



Digital Full Colour Multifunctional System

Free to fit—Perfect for your business

High Productivity

- 100-sheet RSPF scans documents at 52 opm*1 (one-sided)
- Multi bypass tray feeds paper up to 256 g/m² thick
- Print Release function enables printout from any compatible networked MFP*2
- Direct printing of Microsoft® Office (docx, xlsx, pptx) files*³ (option)
- OCR allows users to convert scanned documents into editable Office Open XML (docx, xlsx, pptx) files and searchable PDFs (option)
- Multicrop/Image Crop functions simultaneously scan multiple receipts/photos and save them as separate files
- Supports compact PDF (option)
- For large-volume scanned data, a URL can be generated and shared via e-mail
- Inbound routing lets you forward received faxes to a preset destination (option)

Exceptional Ease of Use

- Easy UI mode on 7.0-inch colour LCD touchscreen
- Dedicated user icons allow quick login to personalised operation screen
- Control panel tilts at various angles for easy access
- Red and green LED lamps light up to notify users of machine/job status
- Small footprint*4 (568 × 630 mm)
- Energy-saving functions include short warm-up time, power consumption of 0.5 W in fax/network standby, and more

Superb Image Quality

- Genuine Adobe[®] PostScript[®] 3[™] (option)
- Sharp's proprietary Auto Colour Mode, further improved for enhanced scan performance
- Automatically makes scan settings according to document type-provides optimal scan results



Secure Information Sharing

- Secondary Ethernet port to support additional network*5
- Wireless connectivity enables easy access from mobile devices and flexible MFP placement (option)
- NFC*6 and QR Code[®] enable easy direct connection between MFP and mobile device
- Supports Sharpdesk Mobile print/scan application*7 and various mobile printing services (option)
- Application Portal offers apps for downloading and installing onto MFP
- Easy access to public cloud services such as OneDrive® for Business via single sign-on (option)
- Sends scanned data via Gmail[™] or Microsoft Exchange/Online accounts
- Sharp OSA (Open Systems Architecture) allows integration with network and cloud-based applications (option)
- Advanced system/data protection and access control, including firmware self-recovery and whitelisting*8

*1: Originals per minute; when feeding A4 (8¹/₂" x 11") sheets.
*2: Contact a Sharp customer representative for details on the record nended maximum

number of connectable MFPs.

*4: "Footprint" refers to the part directly adjacent to the floor or desk space. The numerical value is for the MFP's base unit only.

- *6: Requires third-party Ethernet adaptor that supports two lines.
 *6: The NFC interface is for Android™ devices running Android 9 or earlier. Requires third-party
- NFC card reader
- *7: Availability varies by country/region.*8: Certain functions require optional equipment



BP-30C25Z/BP-30C25ZT

Digital Full Colour Multifunctional System

SPECIFICATIO	NS (tentative)			
General		Document Filing		
Type Engine speed Control panel display Paper size Paper capacity	Desktop A4 (8 ¹ /2" x 11")* ¹ : Max. 25 ppm A3 (11" x 17"): Max. 14 ppm 7.0-inch colour LCD touchscreen Max. A3W (12" x 18"), min. A6 (5 ¹ /2" x 8 ¹ /2")* ² Standard: 350 sheets	Document filing capacity*13 Stored jobs*14 Storage folders	Main and custom folders: 5,000 pages or 500 files Quick file folder: 5,000 pages or 500 files Copy, print, scan, fax Quick file folder, main folder, custom folder (max. 1,000 folders)	
(80 g/m ²)	(250-sheet tray and 100-sheet multi bypass tray) Maximum: 1,850 sheets	Printer		
Paper weight	(350 sheets & optional 3 x 500-sheet tray) Tray 1: 60 g/m ² to 105 g/m ² (16 lbs bond to 28 lbs bond) Trays 2-4 (BP-CS10/DE10): 60 g/m ² to 220 g/m ² (16 lbs bond to 80 lbs cover) Multi bypass tray: 55 g/m ² to 256 g/m ² (13 lbs bond to 140 lbs index)	Resolution Interface Supported OS* ¹⁶	600 x 600 dpi, 9,600 (equivalent) x 600 dpi USB 2.0 (host, high-speed), 10Base-T/100Base-TX/1000Base-T, wireless LAN (IEEE 802.11 b/g/n) ^{*15} Windows Server [®] 2012, Windows Server [®] 2012 R2, Windows Server [®] 2016, Windows Server [®] 2019,	
Warm-up time* ³ Memory Power requirements Power consumption Dimensions (W x D x H) Weight (approx.)	17 sec.*4 5 GB (copy/print shared) 128 GB SSD*5 Rated local AC voltage ±10%, 50/60 Hz Max. 1.44 kW (110 V to 120 V), max. 1.84 kW (220 V to 240 V) 568 x 630 x 653 mm (22 ³ / ₈ " x 24 ¹³ / ₁₆ " x 25 ²³ / ₃₂ ") 54 kg (119.1 lbs)	Network protocols Printing protocols PDL	Windows® 8.1, Windows® 10 Mac OS 10.9, 10.10, 10.11, 10.12, 10.13, 10.14, 10.15 TCP/IP LPR, Raw TCP (port 9100), POP3 (e-mail printing), HTTP, FTP for downloading print files, IPP, SMB, WSD Standard: PCL 6 emulation Option: Adobe® PostScript® 3™ 00 forth for PCL 102 force for 4 deba DestCarist 2	
Copier		Available fonts	80 fonts for PCL, 139 fonts for Adobe PostScript 3	
Original paper size First copy time* ⁶ Continuous copy Resolution Gradation Zoom range	Max. A3 (11" x 17") Colour: 11.0 sec. B/W: 8.0 sec. Max. 9,999 copies Scan (colour): 600 x 600 dpi Scan (B/W): 600 x 600 dpi, 600 x 400 dpi Print: 600 x 600 dpi, 9,600 (equivalent) x 600 dpi (depending on copy mode) Equivalent to 256 levels 25% to 400% (25% to 200% using RSPF) in 1% increments	Facsimile (requires Compression method Communication protocol Transmission time Modem speed Transmission resolution Recording size Memory	s optional MX-FX15) MH/MR/MMR/JBIG Super G3/G3 Less than 3 seconds* ¹⁷ 33,600 bps to 2,400 bps with automatic fallback From Standard (203.2 x 97.8 dpi) to Ultra Fine (406.4 x 391 dpi) A3 to A5 (11" x 17" to 5 ¹ / ₂ " x 8 ¹ / ₂ ") 1 GB (built-in)	
Preset copy ratios	Metric: 10 ratios (5R/5E), inch: 8 ratios (4R/4E)	Greyscale levels	Equivalent to 256 levels	
Colour Scanner Scan method Scan speed* ⁷ Resolution	Push scan (via control panel) Pull scan (TWAIN-compliant application) Colour & B/W: Max. 52 originals/min. Push scan: 100, 150, 200, 300, 400, 600 dpi Pull scan: 75, 100, 150, 200, 300, 400, 600 dpi	*1: Long-edge feeding. *2: Only short-edge feeding can be used with 5 ¹ / ₂ " x 8 ¹ / ₂ " paper. *3: In a standard measurement environment. May vary depending on operating conditions and environment. *4: When starting the MFP via the power button. 28 seconds when starting via the main power switch. *5: SSD capacity depends on procurement and sourcing status. *6: Long-edge feeding of A4 (8 ¹ / ₂ " x 11") sheets from 1st paper tray, using document glass, MFP in fully ready condition. May vary depending on operating conditions and environment. *7: Based on Sharp's A4 standard chart, using document feeder, long-edge feeding, one-sided scanning, and factory default settings. Scan speed		
File formats Scan destinations	50 dpi to 9,600 dpi via user setting* ⁸ TIFF, PDF, PDF/A-1a ^{*3} , PDF/A-1b, encrypted PDF, XPS, compact PDF ^{*10*11} , JPEG ^{*11} , searchable PDF ^{*9} , OOXML (pptx, xlsx, docx) ^{*9} , text (TXT [UTF-8]) ^{*3} , rich text (RTF) ^{*9} Scan to e-mail/desktop ^{*12} /FTP server/network folder (SMB)/ USB drive/local drive	 will vary depending on the type of document and the scan settings. '8: Resolution will vary depending on the size of the scanned area. '9: Requires optional MX-EB20. '10: Requires optional MX-EB19. *11: Colour/greyscale only. *12: Requires Network Scanner Tool Lite. '13: Storage capacity will vary depending on the type of document and the scan settings.' 14: Some features require optional equipment. *15: Requires optional MX-EB18. Availability of this option varies by country/region. *16: Mac OS requires optional MX-FK13. *17: Based on Sharp's standard chart with approx. 700 characters (A4 or 8 ¹/₂" x 11" long-edge feeding) at standard resolution in Super G3 mode, 33,600 bps, JBIG compression. 		
Microsoft, OneDrive, Window of Microsoft Corporation in registered trademarks or tra- registered trademark of DEN	re subject to change without prior notice. ws Server, and Windows are either registered trademarks or trademarks the US and/or other countries. Adobe and PostScript 3 are either ademarks of Adobe in the US and/or other countries. QR Code is a VSO WAVE INCORPORATED in Japan and other countries. Gmail and Google LLC. Mac is a trademark of Apple Inc., registered in the US and	is a product of Qualcomm Tec Qualcomm Incorporated, regi CSR Imaging US, LP, registere	tered trademark of Hewlett-Packard Company. Qualcomm DirectOffice thologies, Inc. and/or its subsidiaries. Qualcomm is a trademark of stered in the US and other countries. DirectOffice is a trademark of d in the US and other countries. All other brand names and product registered trademarks of their respective owners.	

SYSTEM CONFIGURATION

				MX-PU10 Direct Print Expansion Kit	MX-AMX2 Application Communication Module
	and the second s			MX-PK13 PS3 Expansion Kit	MX-AMX3 External Account Module
				MX-PF10 Barcode Font Kit	MX-EB18 Wireless LAN Adaptor
				MX-FX15 Fax Expansion Kit	MX-EB19 Enhanced Compression Kit
	BASE UNIT			MX-FWX1 Internet Fax Expansion Kit	MX-EB20 OCR Expansion Kit
		BP-CS10 500-Sheet Paper Feed Tray		MX-AMX1 Application Integration Module	BP-FR10U Data Security Kit
BP-DS11 Low Stand		BP-DS10 High Stand		BP-DE10 Stand with 2 x 500-Sheet Paper Drawer	
ote: If you install the MFP on a floor, Sharp recommends setting	it up on a stand (either th	e BP-DS11, BP-DS10	or BP-DE10). This	set-up also requires the BP-CS10 p	aper tray option.

Distributed by:



Qualcomm[®] DirectOffice[®]